



Call Draygon 800-724-3610 For All
Lavina Grinders/Polishers by Superabrasive Inc.
Make Your Floor Polishing Jobs A Breeze



7 Pro Single-phase, Variable Speed 2 HP for working on corners and edges



7N Pro Single-phase, Variable Speed 3 HP for working on corners and edges



16 Pro Single-phase, Variable Speed, 3 HP for small and medium residential jobs



20 Pro Single-phase, Variable Speed 4 HP for large residential and small commercial jobs



20N Pro Single-phase Variable Speed 7 HP for large residential and small commercial jobs—also in High Voltage 20N HV Pro model



21-3 Pro Single Phase 220 V 3.4 HP and also 21-1.5 110V 1.5 HP. Ideal for small residential jobs.

NEW! And also available in a 1.5HP, 110V version!



25Pro Three-phase/Single-phase, Variable Speed 10 HP for average and large commercial and I industrial jobs—also in High Voltage 25 HV Pro HV model



25L Pro Three-phase Variable Speed 25 HP for large residential and commercial jobs—also in High Voltage 25L HV Pro model



NEW! The first propane-powered Lavina Pro!

25G Pro Propane Engine 18 HP for medium and large commercial projects



NEW! Featuring Low Profile Base

30L Pro Low Profile Base Three-phase 15 HP Variable Speed. This machine is ideal for big box retail and other commercial projects. Also in a High Voltage 30L HV Pro model



NEW! The first propane-powered Lavina Pro!

30G Pro 18 HP Propane Engine, and a new low profile base for reaching under cabinets and shelving. Ideal for big-box retail and other commercial projects.



32 Pro Six Head, Three-phase, Variable Speed 20 HP for very large commercial and industrial jobs—also in High Voltage 32 HV Pro Model

LAVINA PRO machines

LAVINA 7 PRO, LAVINA 7N PRO, LAVINA 16[®] PRO specifications



LAVINA 7 PRO, LAVINA 7N PRO

Horsepower	2HP, 1.5KW
Voltage*	1ph x 110V
Amperage	15 Amp
Dedicated Breaker Requirement	15 Amp

Weight of Machine	137 lbs / 62 kg
Grinding Pressure	50 lbs / 20kg
Additional Weight	up to 22 lbs / 10 kg
# of Additional Weights	4 x 5.50 lbs / 2.5 kg

Attachment Speed	500-1000 rpm
Working Width	7in / 175mm
Tool Holder Diameter	6.5in / 165mm
Tool Diameter	7in / 175mm

Application	dry
Dust-vacuum	yes
Water feeding	no
Water tank capacity	N/A
Cable Length	57 ft / 17.4 m

Machine Length	38.6in / 980mm
Machine Width	12.6in / 320mm
Machine Height	36.6in / 930mm
Machine Length (pallet)	28.7in / 730mm
Machine Width (pallet)	28.7in / 730mm
Machine Height (pallet)	41in / 1050mm

*Not for use with GFI circuits
 LAVINA 7 PRO is also available in a 220V version:
 LAVINA 7N PRO: 3HP, 220V



LAVINA 16[®] PRO

Horsepower	3HP, 2.2KW
Voltage	1ph x 208-240V
Amperage	12 Amp
Dedicated Breaker Requirement	15 Amp

Weight of Machine	203 lbs / 92 kg
Grinding Pressure	121 lbs / 55kg
Additional Weight	up to 22 lbs / 10 kg
# of Additional Weights	1 x 22 lbs / 10 kg

Attachment Speed	300-1100 rpm
Working Width	16in / 410mm
Tool Holder Diameter	3x6.5in / 3x165mm
Tool Diameter	3x7in / 3x175mm

Application	wet or dry
Dust-vacuum	yes
Water feeding	peripheral
Water tank capacity	2.8gal / 10.5L
Cable Length	57 ft / 17.4 m

Machine Length	45.7in / 1160mm
Machine Width	16.9in / 430mm
Machine Height	42in / 1070mm
Machine Length (pallet)	45.2in / 1150mm
Machine Width (pallet)	28.7in / 730mm
Machine Height (pallet)	45.5in / 1155mm

Draygon Enterprises Inc.
 313 Seaboard Avenue Suite B, Venice FL 34285
 Ray@draygon.com www.draygon.com 800-724-3610

LAVINA PRO machines

LAVINA 20° PRO, LAVINA 20°N PRO, LAVINA 20°N-HV PRO specifications



LAVINA 20° PRO

Horsepower	4HP, 3KW
Voltage	1ph x 208-240V
Amperage	15 Amp
Dedicated Breaker Requirement	15 Amp

Weight of Machine	318 lbs / 144 kg
Grinding Pressure	180 lbs / 65 kg
Additional Weight	up to 48 lbs / 22 kg
# of Additional Weights	1 x 48 lbs / 22 kg

Attachment Speed	300-1100 rpm
Working Width	20in / 510mm
Tool Holder Diameter	3x6.5in / 3x165mm
Tool Diameter	3x9in / 3x225mm

Application	wet or dry
Dust-vacuum	yes
Water feeding	peripheral
Water tank capacity	4.2gal / 16L
Cable Length	57 ft / 17.4 m

Machine Length	53.1in / 1350mm
Machine Width	21.3in / 540mm
Machine Height	43.3in / 1100mm
Machine Length (pallet)	45.2in / 1150mm
Machine Width (pallet)	28.7in / 730mm
Machine Height (pallet)	45.5in / 1155mm

LAVINA 20°N PRO, LAVINA 20°N-HV PRO

Horsepower	7.5HP, 5.5KW
Voltage	1or 3ph x 208-240V
Amperage	30 Amp
Dedicated Breaker Requirement	30 Amp

Weight of Machine	337 lbs / 153 kg
Grinding Pressure	216 lbs / 98 kg
Additional Weight	up to 96 lbs / 74 kg
# of Additional Weights	2 x 48 lbs / 22 kg

Attachment Speed	300-1100 rpm
Working Width	20in / 510mm
Tool Holder Diameter	3x6.5in / 3x165mm
Tool Diameter	3x9in / 3x225mm

Application	wet or dry
Dust-vacuum	yes
Water feeding	peripheral
Water tank capacity	4.2gal / 16L
Cable Length	57 ft / 17.4 m

Machine Length	53.1in / 1350mm
Machine Width	21.3in / 540mm
Machine Height	43.3in / 1100mm
Machine Length (pallet)	45.2in / 1150mm
Machine Width (pallet)	28.7in / 730mm
Machine Height (pallet)	45.5in / 1155mm

LAVINA 20°N PRO is also available in a high voltage version:
LAVINA 20°N-HV PRO: 3phx380/480V, 20 Amp

LAVINA PRO machines

LAVINA 21-1.5, LAVINA 21-3, LAVINA 25[®] PRO, LAVINA 25[®]HV PRO specifications



NEW! And also available in a 1.5HP, 110V version!



LAVINA 21-3, the "economy" LAVINA

Horsepower	3.4HP, 2.5KW
Voltage	1ph x 220V
Amperage	15 Amp
Dedicated Breaker Requirement	15 Amp

Weight of Machine	202 lbs / 92 kg
Grinding Pressure	130 lbs / 59 kg
Additional Weight	2 x 18.5lbs / 2 x 8kg
# of Additional Weights	2 max (18.5lbs, 8kg)

Attachment Speed	1100 rpm
Working Width	20in / 508mm
Tool Holder Diameter	3x7.75in / 3x197mm
Tool Diameter	3x8in / 3x200mm

Application	wet or dry
Dust-vacuum	yes
Water feeding	peripheral
Water tank capacity	5.2gal / 20L
Cable Length	57 ft / 17.4 m

Machine Length	59.1in / 1500mm
Machine Width	21.3in / 540mm
Machine Height	42in / 1070mm
Machine Length (pallet)	43.3in / 1100mm
Machine Width (pallet)	29.5in / 750mm
Machine Height (pallet)	55in / 1400mm

LAVINA 21-3 is also available in a 110V version:

LAVINA 21-1.5: 1.5HP, 110V

LAVINA 25[®] PRO, LAVINA 25[®]HV PRO

Horsepower	10HP, 7.5KW
Voltage	1 or 3ph x 208-240V
Amperage	30 Amp
Dedicated Breaker Requirement	30 Amp

Weight of Machine	439 lbs / 199 kg
Grinding Pressure	306 lbs / 139 kg
Additional Weight	up to 128 lbs / 58 kg
# of Additional Weights	2 x 64 lbs / 29 kg

Attachment Speed	300-1100 rpm
Working Width	25in / 655mm
Tool Holder Diameter	3x6.5in / 3x165mm
Tool Diameter	3x9in / 3x225mm

Application	wet or dry
Dust-vacuum	yes
Water feeding	peripheral
Water tank capacity	4.2gal / 16L
Cable Length	57 ft / 17.4 m

Machine Length	62in / 1575mm
Machine Width	27.6in / 690mm
Machine Height	46in / 1170mm
Machine Length (pallet)	45.2in / 1150mm
Machine Width (pallet)	28.7in / 730mm
Machine Height (pallet)	45.5in / 1155mm

LAVINA 25[®] PRO is also available in a high voltage version:

LAVINA 25[®]HV PRO: 3phx380/480V, 20 Amp

LAVINA PRO machines

LAVINA 25L PRO, LAVINA 25L-HV PRO, LAVINA 25G PRO specifications



NEW! The first propane-powered Lavina Pro!

LAVINA 25L PRO, LAVINA 25L-HV PRO

Horsepower	15HP, 11KW
Voltage	3ph x 208-240V
Amperage	45 Amp
Dedicated Breaker Requirement	45 Amp

Weight of Machine	602 lbs / 274 kg
Grinding Pressure	398 lbs / 181 kg
Additional Weight	up to 128 lbs / 58 kg
# of Additional Weights	2 x 64 lbs / 29 kg

Attachment Speed	300-1100 rpm
Working Width	25in / 655mm
Tool Holder Diameter	3x6.5in / 3x165mm
Tool Diameter	3x9in / 3x225mm

Application	wet or dry
Dust-vacuum	yes
Water feeding	peripheral
Water tank capacity	5.2gal / 20L
Cable Length	57 ft / 17.4 m

Machine Length	74in / 1880mm
Machine Width	27.2in / 690mm
Machine Height	46.5in / 1180mm
Machine Length (pallet)	45.2in / 1150mm
Machine Width (pallet)	28.7in / 730mm
Machine Height (pallet)	60.2in / 1530mm

LAVINA 25L PRO is also available in a high voltage version:

LAVINA 25L-HV PRO: 3phx380/480V, 30 Amp

LAVINA 25G PRO - NEW!

Propane Engine Capacity	603cc, 36.8 cu in
	Kawasaki
Power	18hp/3600min

Weight of Machine	490 lbs / 222 kg
Grinding Pressure	330 lbs / 150 kg
Additional Weight	2 x 64 lbs / 29 kg
# of Additional Weights	2 x 64 lbs / 29 kg

Attachment Speed	1100 rpm
	3600 engine RPM
Working Width	30in / 765mm
Tool Holder Diameter	3x6.5in / 3x165mm
Tool Diameter	3x9in / 3x225mm

Application	wet or dry
Dust-vacuum	yes
Water Feeding	peripheral
Water Tank Capacity	5.2gal / 20L
Propane Tank Capacity	20lbs / 9kg

Machine Length	74in / 1872mm
Machine Width	27in / 682mm
Machine Height	47in / 1179mm
Machine Length (pallet)	45in / 1150mm
Machine Width (pallet)	29in / 730mm
Machine Height (pallet)	59in / 1500mm

Draygon Enterprises Inc.
 313 Seaboard Avenue Suite B, Venice FL 34285
 Ray@draygon.com www.draygon.com 800-724-3610

LAVINA PRO machines

LAVINA 30L PRO, LAVINA 30L-HV PRO, LAVINA 30G PRO specifications



NEW! Featuring the new LP "low profile" base



NEW! The first propane-powered Lavina Pro!

LAVINA 30L PRO, LAVINA 30L-HV PRO

Horsepower	15HP, 11KW
Voltage	3ph x 208-240V
Amperage	45 Amp
Dedicated Breaker Requirement	45 Amp

Weight of Machine	760 lbs / 345 kg
Grinding Pressure	550 lbs / 250 kg
Additional Weight	up to 128 lbs / 58 kg
# of Additional Weights	2 x 64 lbs / 29 kg

Attachment Speed	300-1100 rpm
Working Width	32in / 812mm
Tool Holder Diameter	3x6.5in / 3x165mm
Tool Diameter	3x13.5in / 3x335mm

Application	wet or dry
Dust-vacuum	yes
Water feeding	peripheral
Water tank capacity	5.2gal / 20L
Cable Length	57 ft / 17.4 m

Machine Length	76in / 1930mm
Machine Width	32in / 805mm
Machine Height	47in / 1110mm
Machine Length (packaged)	46in / 1150mm
Machine Width (packaged)	29in / 730mm
Machine Height (packaged)	59in / 1500mm

LAVINA 30L PRO is also available in a high voltage version:

LAVINA 30L-HV PRO: 3phx380/480V, 30 Amp

This model is an LP! It features our new low profile "lip" for reaching beneath cabinets, shelving, and other hard to reach areas!

LAVINA 30G PRO - NEW!

Propane Engine Capacity	603cc, 36.8 cu in
	Kawasaki
Power	18hp/3600min

Weight of Machine	490 lbs / 222 kg
Grinding Pressure	330 lbs / 150 kg
Additional Weight	2 x 64 lbs / 29 kg
# of Additional Weights	2 x 64 lbs / 29 kg

Attachment Speed	100 rpm
	3600 engine RPM
Working Width	30in / 765mm
Tool Holder Diameter	3x6.5in / 3x165mm
Tool Diameter	3x13.5in / 3x335mm

Application	wet or dry
Dust-vacuum	yes
Water Feeding	peripheral
Water Tank Capacity	5.2gal / 20L
Propane Tank Capacity	20lbs / 9kg

Machine Length	76in / 1930mm
Machine Width	32in / 805mm
Machine Height	47in / 1110mm
Machine Length (pallet)	46in / 1150mm
Machine Width (pallet)	29in / 730mm
Machine Height (pallet)	59in / 1500mm

This model is an LP! It features our new low profile "lip" for reaching beneath cabinets, shelving, and other hard to reach areas!

Draygon Enterprises Inc.

313 Seaboard Avenue Suite B, Venice FL 34285
Ray@draygon.com www.draygon.com 800-724-3610

LAVINA PRO machines

LAVINA 32[®] PRO, LAVINA 32[®]HV PRO specifications



LAVINA 32[®] PRO, LAVINA 32[®]HV PRO

Horsepower	20HP, 15KW
Voltage	3ph x 208-240V
Amperage	60 Amp
Dedicated Breaker Requirement	60 Amp

Weight of Machine	760 lbs / 345 kg
Grinding Pressure	550 lbs / 250 kg
Additional Weight	up to 128 lbs / 58 kg
# of Additional Weights	2 x 64 lbs / 29 kg

Attachment Speed	300-1100 rpm
Working Width	32in / 812mm
Tool Holder Diameter	6x6.5in / 6x165mm
Tool Diameter	6x9in / 6x225mm

Application	wet or dry
Dust-vacuum	yes
Water feeding	peripheral
Water tank capacity	12gal / 46L
Cable Length	57 ft / 17.4 m

Machine Length	90.1in / 2335mm
Machine Width	34in / 850mm
Machine Height	44in / 1100mm
Machine Length (packaged)	46in / 1175mm
Machine Width (packaged)	37in / 950mm
Machine Height (packaged)	50in / 1280mm

LAVINA 32[®] PRO is also available in a high voltage version:

LAVINA 32[®]HV PRO: 3phx380/480V, 35 Amp

Draygon Enterprises Inc.
313 Seaboard Avenue Suite B, Venice FL 34285
Ray@draygon.com www.draygon.com 800-724-3610